



RFxx20 CLASSIC TOPCOAT

FIELD OF APPLICATION

Doors and windows, garden furniture, claddings, balconies, enclosures, matchboardings, beams.

INFORMATION

It makes the wood water-repellent, resistant and durable. Do not use on white wood stains, on which the completely colourless Waxy Topcoat RC2030 is recommended. 5-10% dilution with water is possible to improve the application of the product.

INSTRUCTIONS

Stained/impregnated wood. It is possible to apply RFxx20 on a wood treated with low-solid content dyes or wood stains. Once the surface has been cleaned, sand with sandpaper or scotch brite. Then remove the powder and apply 1-2 coats of product.

Coated wood. On a paint finish which is in good condition, it is necessary to sand with 320 grit sandpaper. Clean the surface, then proceed to paint. On a paint finish which is in bad condition, sand with 80-150 grit sandpaper to bring the wood back to the raw condition. Clean the surface and proceed to paint. Application of 1-2 coats of Wood Stain RMxx10 or Gel Wood Stain RGxx80 before RFxx20 is recommended.

MAINTENANCE

In case of objects, which are very exposed to the atmospheric agents, it is sufficient to treat only the parts that begin to deteriorate. Slightly sand the object with 220-320 grit sandpaper, remove the powder and apply one coat. On the most deteriorated parts it is possible to apply a second coat. If the object is not much exposed to the atmospheric agents, the maintenance operations will be less frequent. To extend the protective action of the film and the aspect of the woodwork it is recommended to clean with Neutral Detergent T.Clean RR1050 and Brightener T.Top+ RR1250 every six months. Avoid aggressive detergents.

OVERCOATING

Classic Topcoat RFxx20, UV Defender Topcoat RQxx70 and Waxy Topcoat RCxx30.

PACKAGING

0,75 L

2,5 L

10 L



Storage
> 5°C



Painting
> 10°C



Ready to use



Brush
Spray gun



Yield
10 m²/L



Mix it well
before use



Drying time
between the coats
2-6 h



Final drying time
12 h



Solid content
35 ± 3 %



Viscosity
DIN8 14 ± 3"



Specific weight
1,05 ± 0,1 g/cm³



pH
8,5 ± 1,0



Gloss level
30 for RF1020
60 for RF1120



RF1020
TRANSPARENT MATT



RF1120
TRANSPARENT SEMI-GLOSSY