



# RMxx10 WOOD STAIN

## FIELD OF APPLICATION

Doors and windows, garden furniture, claddings, balconies, enclosures, matchboardings, beams.

## INFORMATION

It decorates and protects the wood from atmospheric agents and UV light, excepted the transparent version.

## INSTRUCTIONS

*Raw wood.* Sand the support with 150 grit sandpaper, clean the surface from the sanding powder and apply 1-2 coats of RMxx10 range.

*Stained/impregnated wood.* It is possible to apply RMxx10 on a wood treated with low-solid content dyes or wood stains. Once the surface has been cleaned, sand with sandpaper or scotch brite. Then remove the powder and apply 1-2 coats of product.

*Coated wood.* Sand with 80-150 grit sandpaper and bring the wood back to the raw condition. Clean the surface and proceed to impregnate.

## OVERCOATING

Classic Topcoat RFxx20, UV Defender Topcoat RQxx70, Waxy Topcoat RCxx30 and Decogrip Solution RE20xx.

## PACKAGING

0,75 L                                  2,5 L                                  10 L \*

\* only RM1010, RM1210, RM1310, RM1410, RM1610, RM2010

- Storage > 5°C
- Painting > 10°C
- Ready to use
- Brush  
Spray gun  
Cloth
- Yield  
12 m<sup>2</sup>/L
- Mix it well before use
- Drying time between the coats  
1-2 h
- Final drying time  
3 h
- Solid content  
11 ± 3 %
- Viscosity  
DIN2 50 ± 10"
- Specific weight  
1,05 ± 0,1 g/cm<sup>3</sup>
- pH  
8,5 ± 1,0



- RM1010**  
TRANSPARENT
- RM1110**  
TEAK
- RM1210**  
CHESTNUT-BRIGHT WALNUT
- RM1310**  
WALNUT
- RM1410**  
DARK WALNUT
- RM1510**  
DARK-BROWN WALNUT
- RM1610**  
PINE-LARCH
- RM1710**  
DURMAST
- RM1810**  
MAHOGANY
- RM2010**  
WHITE\*

\* The white version is certified in A+ class regarding indoor air emissions  
\*\*Except for transparent and white versions